Applicable MIL-STD-810C/D/E/F

Applicable	810C	810D	810E	810F
MIL-STD	Methods Procedures	Methods Procedures	Methods Procedures	Methods Procedures
Low Pressure	500.1 1	500.2 1,2	500.3 1,2	500.4 1
High Temperature	501.1 1,2	501.2 1,2	501.3 1,2	501.4 1,2
Low Temperature	502.1 1	502.2 1,2	502.3 1,2	502.4 1,2
Temp. Shock	503.1 1	503.2 1	503.3 1	503.4 1
Solar Radiation	505.1 1	505.2 1	505.3 1	505.4 1,2
Rain	506.1 2	506.2 2	506.3 1,2	506.4 1,2
Humidity	507.1 2	507.2 2,3	507.3 2,3	507.4 1
Salt Fog	509.1 1	509.2 1	509.3 1	509.4 1
Dust	510.1 1	510.2 1	510.3 1	510.4 1
Vibration	514.2 8,10	514.3 1	514.4 1	514.5 1
Shock	516.2 1,2,5	516.3 1,4	516.4 1,4	516.5 1,4

Gerierai			
Frequency Range(MHz)	VHF: 136-174 UHF: 400-420 440-470 420-450 450-470 420-470 470-490		
Channel Capacity	16		
Channel Spacing(KHz)	25 /12.5		
Operating Voltage(v)	7.4		
Battery	1200mAh (Li-ion)		
Battery Life (5-5-90 Duty Cycle)			
1200mAh Li-Ion battery	More than 9 hours		
1300mAh Ni-MH battery	More than 9 hours		
2000mAh Li-Ion battery	More than 14 hours		
Frequency Stability(ppm)	± 2.5		
Operating Temperature(${\mathbb C}_{)}$	-20~+55		
Antenna Impedance (Ω)	50		
Dimensions (H × W × D)(with battery, without antenna)(mm)	119 × 55 × 33		
Weight (with antenna & battery)(g)	270		

RF Power Output	5W/2W(VHF) 5W/2W(UHF)
Modulation	F3E
Spurious and Harmonics	-36dBm<1GHz -30dBm>1GHz
FM Noise	40/35dB
Audio Distortion	≤5 %

All Specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development.

Sensitivity	0.25/0.28 μ V
Selectivity	70/60dB
Intermodulation	≥65dB
Spurious Response Rejection	≥70dB
S/N	45/40dB
Rated Audio Power Output	800mW
Rated Audio Distortion	≤5%



www.hytera.cn

Hytera Communications Corporation Limited

HYT is a registered trademark of Hytera

Address: HYT Tower, Hi-Tech Industrial Park North, Beihuan RD.,

Nanshan District, Shenzhen, China Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057

© 2010 Hytera, Co., Ltd. All Rights Reserved.

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant re sponsibility.Little difference between real product and product indicated by printing materials will occur by printing reason.

Your Local Dealer

The leading provider of professional wireless communication equipment and solutions



TC-610

Professional Two-way Radio







- Dust/Water Protection Class IP66
- Powerful Audio and Wide Communication Range
- Reliable Mechanical Design
- Innovative Industrial Design



UK100628A



TC-610

Professional Two-way Radio

Super Features -

Dust/Water Protection Class IP66

In harsh, noisy and dusty working conditions such as construction sites and engineering sites, your radio is apt to be smudged. The TC-610 portable radios are IP66-rated and have excellent dust/water protection performance. The IP66 protection allows you to wash off mud and dust on your radio. A water jet (40mm ⊄) from a nozzle, which is projected from any direction against your radio for up to one minute, must not have any harmful effect. Your radio could be dried to operate normally after you

Powerful Audio and Wide Communication Range

Superior audio quality is the premise for your team to work efficiently in noise environments. A powerful speaker with size of 45mm & (36mm & speaker for common radios) ensures clear and crisp sound, even in noisy environments. You can also use high transmit power for wide communication coverage.

Reliable Mechanical Design

Battery latch is apt to become loose after long time use, and even occasionally causes your radio to shut off automatically. All these will affect your working efficiency. HYT proprietary battery latch mechanism is applied to TC-610 radios. It delivers secure connection between battery and radio. no matter how long the radio has been in use.

Innovative Industrial Design

The TC-610 abandons conventional black body, and employs fashionable yellow rubber housing, making the radio more comfortable to handle.

* IP66 water protection ensures the radio to be protected against a water jet for one minute. The diameter of the water jet is 40 mm

High/Low Power Switchable

power when communicating within limited range coverage or switch to high power when further distance is required. High transmit power optimizes range coverage while low transmit power conserves battery consumption, all at the user's

Programmable 12.5kHz / 25kHz Channel

The feature enables flexibility and easy migration of channel spacing requirements when the need arises, with no need to buy new radios.

Allows users to monitor the activity on the current channel. The feature is especially helpful for receiving a weak signal.

Battery Save

The Battery Save feature is automatically activated once no activity on the channel and no operation performed, for extended operation time.

Low Battery Alert

Alert users to recharge the battery should the battery level run low.

Busy Channel Lockout

Time-out Timer

The feature allows for more efficient use of channels by limiting the amount of time of each transmission.

PC Programmable

Wired Clone

CTCSS/CDCSS

Set up workgroups/users with unique CDCSS/CTCSS to prevent unwanted conversations on the same frequency.







Selectable Squelch Level (0-9)

Helps minimize interference from undesired weak signals and helps weak signals be heard.

Channel Scan

The channel scan feature enables the radio to continuously scan each channel in the scan list for activity. Simply press a side function button to activate scanning. When activity is detected on a channel the scan process will stop and you will hear the transmission.

Voice Operated Transmit (VOX)

Enjoy the convenience of hands-free operation when used with optional accessories.

Recommended Applications ———

Hotel Construction sites

Manufacturing

Property management Warehousing Ports

Accessories

Standard

tching Power Adapter (different P/N for different countries and areas)

U/V Antenna MCU Charger CH10A03 Belt Clip BC12 Li-ion Battery (1200mAh) BL1204

Optional Accessories





















